

BR series 19" Wall-Mount Solution



For the environment where physical floor space is at premium, wall-mount rack is an excellent way to provide a flexible rackmount solution. The robust and cost efficient BR series wall-mount rack is ideal for telecom, academic retail, hospital, warehouse, and other applications with space limited areas.

ISO-Certified

9001 14001

The design and manufacturing process of the series achieves the BSI ISO9001 quality control plus ISO14001 environment standard.

50 kg

110 lb

Designed for wall-mount application, the BR series rack holds 50 kg / 110 lb load rating.

Key Benefits

>>> Strong Construction

Fully welded construction for strength

>>> Floor-Support Available

Optional casters available so that the wall-mount rack can be placed on floor.

>>> Convenient Top / Bottom Cable Access

Enhance cabling and patch cord installation

>>> Front Door with Tempered Glass

The fully enclosed rack provides protection from dust in crowd area. Glass door maximize viewing of equipment.

>>> Reversible Hinged Door

User friendly design provides left / right door open flexibility

>>> Lockable Door for Security

Front doors and side panels installed with mechanical locks for rack access security

>>> Removable Front Door / Side Panels

Design for flexible and easier installation.

>>> Optional Fan Kit Available

Promote proper cooling by fan kits and filters

>>> Variety of Dimensions

Height range from 6U to 17U. Depth range from 500 mm to 600 mm.

>>> Fully Assembled

On-site assembly is not required

Standard Package / Size

	Model No.	Width		Depth		Height			
						Overall		Effective	
		mm	inch	mm	inch	mm	inch	mm	inch
6U	BR-6.5	600	24"	537	21"	343	14"	267	11"
	BR-6.6	600	24"	637	25"	343	14"	267	11"
9U	BR-9.5	600	24"	537	21"	477	19"	400	16"
	BR-9.6	600	24"	637	25"	477	19"	400	16"
12U	BR-12.5	600	24"	537	21"	610	24"	533	21"
	BR-12.6	600	24"	637	25"	610	24"	533	21"
15U	BR-15.5	600	24"	537	21"	743	29"	667	26"
	BR-15.6	600	24"	637	25"	743	29"	667	26"
17U	BR-17.5	600	24"	537	21"	832	33"	756	30"
	BR-17.6	600	24"	637	25"	832	33"	756	30"

**Custom size on request



Configuration

Static Loading: 50 kg / 110 lb

Color : White

Main Framework

Vented Top Cover w/ Cable Access Channel

19" Rails, Front Pair

Front Glass Door w/ Lock

Detachable Steel Rear Panel

Side Panel w/ Lock, Pair

M6 Screw Fixing, Pack of 20

Standard Color

- White (RAL 9016)

** Custom color on request

Optional Accessories

Cable Management

CMP-1B	1U cable management panel
CMP-2B	2U cable management panel

Cooling Fan Unit

BR-F2	Top fan tray w/ 2 fans
--------------	------------------------

Shelf, 19" mounting

MS19	Cantilever shelf, 190 mm deep, 20 kg loading
MS40	Cantilever shelf, 400 mm deep, 20 kg loading

Caster

MC	Lockable caster, set of 4
-----------	---------------------------

Rackmount PDU

H8UK90-13A_BS/3B-1	Basic PDU, 8-way (1.25U)
H7UK90-13A_BS/3B-1	Basic PDU, 7-way (1.25U)
H6UK90-13A_BS/3B-1	Basic PDU, 6-way (1.25U)
H5UK90-13A_BS/3B-1	Basic PDU, 5-way (1.25U)
H4UK90-13A_BS/3B-1	Basic PDU, 4-way (1.25U)
H7UK90-13A-MD_BS/3B-1	Metered PDU, 7-way (1.25U)
H6UK90-13A-MD_BS/3B-1	Metered PDU, 6-way (1.25U)
H5UK90-13A-MD_BS/3B-1	Metered PDU, 5-way (1.25U)
H4UK90-13A-MD_BS/3B-1	Metered PDU, 4-way (1.25U)

* IEC C13 / C19 outlet available