



### Benefits

- ▶ 2U 17" / 19" LCD console drawer
- ▶ Dual slide - LCD and keyboard slide independently
- ▶ 1280 x 1024 native resolution / 16.7M colors
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ Short depth design of 480mm
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty ( upgradable up to 5 years )

### Options

- DVI-D / HDMI 1.2 video input
- S-Video + Composite ( BNC )
- Audio input & output
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available
- Touchscreen : Projected Capacitive 10-pt / Resistive 1-pt

## Product Specifications

Console Port	
Video input	VGA
KB / MS	USB interface
VGA console 6ft cable : CB-6A	Drawer end : DB-15 + USB type A x 2 Server end : DB-15 + USB type A x 2

Video Option		
Digital	DVI	DVI-D single link
	HDMI	HDMI 1.2 / HDCP 1.1
Analog	S-Video ( 4-pin )	NTSC & PAL
	Composite ( BNC )	NTSC & PAL

LCD Panel	RKP2417	RKP2419
Panel size ( diagonal )	17"	19"
Native resolution	1280 x 1024	1280 x 1024
Brightness ( cd/m <sup>2</sup> )	250	250
Contrast ratio ( typ. )	1000 : 1	1000 : 1
Colors	16.7 M	16.7 M
Viewing angle ( L/R/U/D )	85/85/80/80	85/85/80/80
Response time ( ms )	5	5
Dot pitch ( mm )	0.264	0.294
Display area ( mm )	337.92H x 270.33V	376.32H x 270.33V
Surface treatment	Haze 25%, Hard-coating	
Surface hardness	3H	
Backlight type	LED	
MTBF (hrs)	30,000	

Audio Option		
Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 22W / Max. 55W
	Power saving mode	Max. 2W / Max. 34W
	Power button off	Max. 1W / Nil

Physical		RKP2417	RKP2419
Product ( W x D x H )	Single console	442 x 480 x 88 mm 17.4 x 18.9 x 3.5 inch	442 x 480 x 88 mm 17.4 x 18.9 x 3.5 inch
	Console w/ KVM	442 x 480 x 88 mm 17.4 x 18.9 x 3.5 inch	442 x 480 x 88 mm 17.4 x 18.9 x 3.5 inch
Packing ( W x D x H )	Single console / Console w/ KVM	585 x 620 x 190 mm 23 x 24.4 x 7.5 inch	585 x 620 x 190 mm 23 x 24.4 x 7.5 inch
	Net weight	Single console 20.4 kg / 44.9 lb	20.5 kg / 45.1 lb
Gross weight	Single console	24.8 kg / 54.6 lb	24.8 kg / 54.6 lb
	Console w/ KVM	27 kg / 59.4 lb	27.4 kg / 60.3 lb

\* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

Mounting Distance		RKP2417	RKP2419
Single console drawer / Console w/ KVM drawer		490 ~ 700 mm 19.3 ~ 27.6 inch	490 ~ 700 mm 19.3 ~ 27.6 inch

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS3 & REACH compliant

# RKP2417 / RKP2419 models w/ KVM

**X** stands for 17" or 19" LCD size.

<b>2K KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>
	0	0	RKP241X - 801D

**2K KVM Cable**



CH - 6D (6 ft)  
DVI-D KVM cable




CH - 6H (6 ft)  
HDMI KVM cable

Resolution: 16:9 - max. 2560 x 1440  
Support \*\*: 16:10 - max. 1920 x 1200  
4:3 - max. 1600 x 1200

<b>DVI-D KVM</b>	<b>IP</b>	<b>Remote</b>	<b>12-port</b>
	0	0	RKP241X - 1201D

**DVI-D USB KVM Cable**


Resolution: 16:10 - max. 1920 x 1200  
Support \*\*: 16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200




CI - 6 (6 ft)  
CI - 15 (15 ft)

<b>Cat6 Matrix KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>	<b>32-port</b>
	1	1	-	RKP241X - MUIP1613	RKP241X - MUIP3213
	2	1	-	RKP241X - MUIP1624	RKP241X - MUIP3224
	0	1	-	RKP241X - MU1602	RKP241X - MU3202
	0	2	-	RKP241X - MU1603	RKP241X - MU3203
	0	3	-	RKP241X - MU1604	RKP241X - MU3204


**Cat6 KVM Dongle**




DG - 100P  
DP - USB dongle




DG - 100H  
HDMI - USB dongle



DG - 100SD  
DVI - USB dongle



DG - 100S  
VGA - USB dongle




DG - 100  
VGA - PS/2 dongle

Resolution: 16:10 - max. 1920 x 1200  
Support \*\*: 16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200


<b>Cat6 Combo KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>	<b>32-port</b>
	1	0	RKP241X - UIP802	RKP241X - UIP1602	RKP241X - UIP3202
	0	1	RKP241X - U802	RKP241X - U1602	RKP241X - U3202
	0	0	RKP241X - U801	RKP241X - U1601	RKP241X - U3201

<b>DB-15 Matrix KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>
	1	1	RKP241X - MIP813	RKP241X - MIP1613
	2	1	RKP241X - MIP824	RKP241X - MIP1624
	0	1	RKP241X - M802	RKP241X - M1602
	0	2	RKP241X - M803	RKP241X - M1603
	0	3	RKP241X - M804	RKP241X - M1604


**DB-15 VGA USB KVM Cable**



CB - 6 (6 ft)



CB - 10 (10 ft)





CB - 15 (15 ft)

Resolution: 16:10 - max. 1920 x 1200  
Support \*\*: 16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200


<b>DB-15 Combo KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>
	1	0	RKP241X - IP802	RKP241X - IP1602
	0	1	RKP241X - 802	RKP241X - 1602
	0	0	RKP241X - S801	RKP241X - S1601

## Standard Keyboard


**Ge** G keyboard integrated with touchpad










**Gb** G keyboard integrated with trackball



### Supporting layouts

**America**  United States

**EMEA**  United Kingdom  Germany  France  Spain  Italy

**Asia**  Japan  Korea

## Keyboard Options

\* US layout only

**Me** Mac keyboard with touchpad



**Se** S keyboard with touchpad

**Mb** Mac keyboard with trackball

**Sb** S keyboard with trackball

