



Benefits

- ▶ 2U 17" LCD console drawer
- ▶ Dual slide - LCD and keyboard slide independently
- ▶ 1920 x 1080 native resolution / 16.7M colors (8-bit)
- ▶ DVI-D + VGA video input / USB KB / MS
- ▶ 104-key keyboard with either touchpad or trackball
- ▶ Short depth design of 480mm
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty (upgradable up to 5 years)

Options

- HDMI 1.3 / DP 1.0 video input
- 3G / HD / SD-SDI Broadcast-grade input
- Composite (BNC)
- Audio input & output
- DC power : 12V / 24V / 48V / 125V
- MAC or SUN Micro keyboard options available
- Touchscreen : Projected Capacitive 10-pt / Resistive 1-pt

Product Specifications

Console Port	
Video input	VGA + DVI-D single link
KB / MS	USB interface
VGA console 6ft cable : CB-6A or DVI-D console 6ft cable : CX-6A	Drawer end : DB-15 + USB type A x 2 Server end : DB-15 + USB type A x 2 Drawer end : DVI-D + USB type A x 2 Server end : DVI-D + USB type A x 2

Video Option		
Digital	HDMI	HDMI 1.4 / HDCP 1.4
	Display port	DP 1.0 / HDCP 1.3
Analog	Composite (BNC)	NTSC & PAL

LCD Panel	
Panel size (diagonal)	17.3"
Native resolution	1920 x 1080
Brightness (cd/m ²)	300
Contrast ratio (typ.)	1000 : 1
Colors	16.7 M, 8-bit
Viewing angle (L/R/U/D)	89/89/89/89
Response time (ms)	5.5
Dot pitch (mm)	0.1989
Display area (mm)	381.888H x 214.812V
Surface treatment	Anti-glare, Hard-coating
Surface hardness	3H
Backlight type	LED
MTBF (hrs)	15,000

Audio Option		
Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 14W / Max. 45W
	Power saving mode	Max. 2W / Max. 34W
	Power button off	Max. 1W / Nil

Physical		
Product (W x D x H)	Single console	442 x 480 x 88 mm 17.4 x 18.9 x 3.5 inch
	Console w/ KVM	442 x 480 x 88 mm 17.4 x 18.9 x 3.5 inch
Packing (W x D x H)	Single console / Console w/ KVM	590 x 620 x 190 mm 23.2 x 24.4 x 7.5 inch
Net weight	Single console	20.4 kg / 44.9 lb
	Console w/ KVM	21.1 kg / 46.4 lb
Gross weight	Single console	24.8 kg / 54.6 lb
	Console w/ KVM	27 kg / 59.4 lb

* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration (11ms duration)
Vibration	10~300Hz 0.5G RMS random vibration

Mounting Distance	
Single console drawer / Console w/ KVM drawer	490 ~ 700 mm 19.3 ~ 27.6 inch

Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS3 & REACH compliant


RKP2417F models w/ KVM

** Resolution related to LCD specification






2K KVM	IP	Remote	8-port
	0	0	RKP2417F - 801D

2K KVM Cable		Resolution 16:9 - max. 2560 x 1440 Support **: 16:10 - max. 1920 x 1200 4:3 - max. 1600 x 1200
 CH - 6D (6 ft) DVI-D KVM cable	 CH - 6H (6 ft) HDMI KVM cable	

DVI-D KVM	IP	Remote	12-port
	0	0	RKP2417F - 1201D




DVI-D USB KVM Cable		Resolution 16:10 - max. 1920 x 1200 Support **: 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200	 CI - 6 (6 ft) CI - 15 (15 ft)

Cat6 Matrix KVM	IP	Remote	8-port	16-port	32-port
	1	1	-	RKP2417F - MUIP1613	RKP2417F - MUIP3213
	2	1	-	RKP2417F - MUIP1624	RKP2417F - MUIP3224
	0	1	-	RKP2417F - MU1602	RKP2417F - MU3202
	0	2	-	RKP2417F - MU1603	RKP2417F - MU3203
	0	3	-	RKP2417F - MU1604	RKP2417F - MU3204

Cat6 KVM Dongle		
 DG - 100P DP - USB dongle	 DG - 100H HDMI - USB dongle	 DG - 100SD DVI - USB dongle
 DG - 100S VGA - USB dongle	 DG - 100 VGA - PS/2 dongle	
Resolution 16:10 - max. 1920 x 1200 Support **: 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200		

Cat6 Combo KVM	IP	Remote	8-port	16-port	32-port
	1	0	RKP2417F - UIP802	RKP2417F - UIP1602	RKP2417F - UIP3202
	0	1	RKP2417F - U802	RKP2417F - U1602	RKP2417F - U3202
	0	0	RKP2417F - U801	RKP2417F - U1601	RKP2417F - U3201

DB-15 Matrix KVM	IP	Remote	8-port	16-port
	1	1	RKP2417F - MIP813	RKP2417F - MIP1613
	2	1	RKP2417F - MIP824	RKP2417F - MIP1624
	0	1	RKP2417F - M802	RKP2417F - M1602
	0	2	RKP2417F - M803	RKP2417F - M1603
	0	3	RKP2417F - M804	RKP2417F - M1604



DB-15 VGA USB KVM Cable		
 CB - 6 (6 ft)	 CB - 10 (10 ft)	 CB - 15 (15 ft)
Resolution 16:10 - max. 1920 x 1200 Support **: 16:9 - max. 1920 x 1080 4:3 - max. 1600 x 1200		

DB-15 Combo KVM	IP	Remote	8-port	16-port
	1	0	RKP2417F - IP802	RKP2417F - IP1602
	0	1	RKP2417F - 802	RKP2417F - 1602
	0	0	RKP2417F - S801	RKP2417F - S1601









Standard Keyboard

Ge G keyboard integrated with touchpad

Gb G keyboard integrated with trackball



Supporting layouts

America		United States
EMEA	    	United Kingdom Germany France Spain Italy
Asia	 	Japan Korea

Keyboard Options

* US layout only

Me Mac keyboard with touchpad



Se S keyboard with touchpad

Mb Mac keyboard with trackball

Sb S keyboard with trackball

