



### Benefits

- ▶ 1U 17" / 19" LCD console drawer
- ▶ 1280 x 1024 native resolution / 16.7M colors
- ▶ 104-key keyboard with a true optical mouse
- ▶ One Man installation design
- ▶ Enhanced aesthetics with molded front handle and two point lock
- ▶ 2-year standard warranty ( upgradable up to 5 years )

### Options

- DVI-D / HDMI 1.2 video input
- S-Video + Composite ( BNC )
- Audio input & output
- DC power : 12V / 24V / 48V / 125V

## Product Specifications

Console Port	
Video input	VGA
KB / MS	USB interface
VGA console 6ft cable : CB-6A	Drawer end : DB-15 + USB type A x 2 Server end : DB-15 + USB type A x 2

Video Option		
Digital	DVI	DVI-D single link
	HDMI	HDMI 1.2 / HDCP 1.1
Analog	S-Video ( 4-pin )	NTSC & PAL
	Composite ( BNC )	NTSC & PAL

LCD Panel	RKP7	RKP9
Panel size ( diagonal )	17"	19"
Native resolution	1280 x 1024	1280 x 1024
Brightness ( cd/m <sup>2</sup> )	250	250
Contrast ratio ( typ. )	1000 : 1	1000 : 1
Colors	16.7 M	16.7 M
Viewing angle ( L/R/U/D )	85/85/80/80	85/85/80/80
Response time ( ms )	5	5
Dot pitch ( mm )	0.264	0.294
Display area ( mm )	337.92H x 270.33V	376.32H x 270.33V
Surface treatment	Haze 25%, Hard-coating	
Surface hardness	3H	
Backlight type	LED	
MTBF (hrs)	30,000	

Audio Option		
Input	Connector	3.5mm stereo jack
	Impedance / Power level	30kΩ / 750mV
Output	Connector	3.5mm stereo jack
	Resistance / Power level	30kΩ / 2.8V
Speaker	Dual stereo	2W x 2

Power		
Input	Auto-sensing 100 to 240VAC, 50 / 60Hz	
Consumption (console / KVM)	Screen on	Max. 22W / Max. 55W
	Power saving mode	Max. 2W / Max. 34W
	Power button off	Max. 1W / Nil

Physical		RKP7	RKP9
Product ( W x D x H )	Single console	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch	442 x 700 x 44 mm 17.4 x 27.6 x 1.73 inch
	Console w/ KVM	442 x 650 x 44 mm 17.4 x 25.6 x 1.73 inch	442 x 700 x 44 mm 17.4 x 27.6 x 1.73 inch
Packing ( W x D x H )	Single console / Console w/ KVM	595 x 860 x 140 mm 23.4 x 33.9 x 5.5 inch	595 x 910 x 140 mm 23.4 x 35.8 x 5.5 inch
	Net weight	Single console 14.3 kg / 31.5 lb	15.3 kg / 33.7 lb
Gross weight	Console w/ KVM	19.1 kg / 42 lb	20.1 kg / 44.2 lb
	Single console	15.3 kg / 33.7 lb	16.3 kg / 35.9 lb
Console w/ KVM	21.1 kg / 46.4 lb	22.1 kg / 48.6 lb	

\* All dimensions stated are subject to change if options are selected / integrated to base model part codes

Environment	
Operating temp.	0 to 55°C degree
Storage temp.	-20 to 60°C degree
Operating humidity	20~90%, non-condensing
Storage humidity	5 ~90%, non-condensing
Operating altitude	16,000 ft
Non-operating altitude	40,000 ft
Shock	10G acceleration ( 11ms duration )
Vibration	10~300Hz 0.5G RMS random vibration

Mounting Distance	RKP7	RKP9
Single console drawer / Console w/ KVM drawer	660 ~ 870 mm 26 ~ 34.3 inch	710 ~ 920 mm 28 ~ 36.2 inch


Compliance	
EMC	FCC & CE certified
Safety	CE / LVD certified
Environment	RoHS3 & REACH compliant

# RKP7 / RKP9 models w/ KVM


**X** stands for 17" or 19" LCD size.

<b>2K KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>
	0	0	RKPX - 801D

**2K KVM Cable**



**CH - 6D (6 ft)**  
DVI-D KVM cable




**CH - 6H (6 ft)**  
HDMI KVM cable

Resolution: 16:9 - max. 2560 x 1440  
Support \*\*: 16:10 - max. 1920 x 1200  
4:3 - max. 1600 x 1200

<b>DVI-D KVM</b>	<b>IP</b>	<b>Remote</b>	<b>12-port</b>
	0	0	RKPX - 1201D

**DVI-D USB KVM Cable**


Resolution: 16:10 - max. 1920 x 1200  
Support \*\*: 16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200




**CI - 6 (6 ft)**  
**CI - 15 (15 ft)**

<b>Cat6 Matrix KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>	<b>32-port</b>
	1	1	-	RKPX - MUIP1613	RKPX - MUIP3213
	2	1	-	RKPX - MUIP1624	RKPX - MUIP3224
	0	1	-	RKPX - MU1602	RKPX - MU3202
	0	2	-	RKPX - MU1603	RKPX - MU3203
	0	3	-	RKPX - MU1604	RKPX - MU3204


**Cat6 KVM Dongle**




**DG - 100P**  
DP - USB dongle




**DG - 100H**  
HDMI - USB dongle



**DG - 100SD**  
DVI - USB dongle



**DG - 100S**  
VGA - USB dongle




**DG - 100**  
VGA - PS/2 dongle

Resolution: 16:10 - max. 1920 x 1200  
Support \*\*: 16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200


<b>Cat6 Combo KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>	<b>32-port</b>
	1	0	RKPX - UIP802	RKPX - UIP1602	RKPX - UIP3202
	0	1	RKPX - U802	RKPX - U1602	RKPX - U3202
	0	0	RKPX - U801	RKPX - U1601	RKPX - U3201

<b>DB-15 Matrix KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>
	1	1	RKPX - MIP813	RKPX - MIP1613
	2	1	RKPX - MIP824	RKPX - MIP1624
	0	1	RKPX - M802	RKPX - M1602
	0	2	RKPX - M803	RKPX - M1603
0	3	RKPX - M804	RKPX - M1604	


**DB-15 VGA USB KVM Cable**



**CB - 6 (6 ft)**



**CB - 10 (10 ft)**




**CB - 15 (15 ft)**

Resolution: 16:10 - max. 1920 x 1200  
Support \*\*: 16:9 - max. 1920 x 1080  
4:3 - max. 1600 x 1200




<b>DB-15 Combo KVM</b>	<b>IP</b>	<b>Remote</b>	<b>8-port</b>	<b>16-port</b>
	1	0	RKPX - IP802	RKPX - IP1602
	0	1	RKPX - 802	RKPX - 1602
	0	0	RKPX - S801	RKPX - S1601

## Keyboard

**G** G keyboard



### Supporting layouts

<p><b>America</b></p> <p>United States</p>	
<p><b>EMEA</b></p> <p>United Kingdom    Germany    France    Spain    Italy</p>	
<p><b>Asia</b></p> <p>Japan    Korea</p>	



**WOM-01**  
Wired mini USB optical mouse